LEGEND VALVE

www.legendvalve.com
1-800-752-2082

SUBMITTAL SHEET

JOB NAME | ITEM TAG

JOB LOCATION | PART NUMBER

CONTRACTOR | DATE

ENGINEER APPROVAL | DATE

SCHEDULE 40 BLACK AND GALVANIZED NIPPLES

Nipples, Nipple Assortments, Nipple Runs, Cut-Length Pipe and Oil Tank Legs

Produced in an ISO 9001 registered facility.

Manufactured from Schedule 40 continuous-weld steel pipe with a yield strength minimum of 28,000 psi.

Offered in 1/8" through 4" pipe diameters, in lengths Close through 12".

Boxed assortment packs and runs in 1/2", 3/4", 1" and 1-1/4" pipe diameters are also available.

Bundled and capped black or galvanized cut-length pipe are available in 1/2" through 2" pipe diameters, in lengths 18", 24", 30", 36", 48", 60" and 72". 2-1/2" black cut-length pipe is also available, in 15", 18" and 24" lengths.

All nipples are threaded at both ends, except for the **black oil tank legs,** which are threaded-one-end only

1-1/4" black oil tank legs are available in 9", 10", 11", 12", 13" and 14" lengths.

Packaged in double-corrugated, oil-resistant boxes marked with an English description.

American Society for Testing and Materials (A.S.T.M.):

ASTM A53: Standard specification for pipe, steel, black and hot-dipped zinc coated, welded and seamless.

ASTM A733: Standard specification for welded and seamless carbon steel and austenitic stainless steel pipe nipples.

ASTM A123: Standard specification for zinc coating galvanization, hot-dip application.

American National Standards Institute (A.N.S.I.):

ANSI B36.1: Welded and seamless wrought steel pipe.
ANSI/ASME B1.20.1: Threads, pipe—general purpose (inch).

UPC/IAPMO:

California lead plumbing law compliant: File #6047
NSF Standard 61-4 compliant

MATERIAL SPECIFICATION

PART	MATERIAL	SPECIFICATION
1. All black & galvanized nipples	Steel	ASTM A53 & ANSI B36.1

SCHEDULE 40 BLACK AND GALVANIZED NIPPLE ASSORTMENTS

Part #	SIZES	LENGTH - IN. Close	1-1/2"	2"	2-1/2"	3"	3-1/2"	4"	4-1/2"	5"	5-1/2"	6"	TOTAL PIECES
black nipple run:													
355-256	1/2"	1	1	1	1	1	1	1	1	1	1	1	11
355-257	3/4"	1	1	1	1	1	1	1	1	1	1	1	11
355-258	1"	1	0	1	1	1	1	1	1	1	1	1	10
355-259	1-1/4"	1	0	1	1	1	1	1	1	1	1	1	10
355-268	1-1/2"	1	0	1	1	1	1	1	1	1	1	1	10
355-269	2"	1	0	0	1	1	1	1	1	1	1	1	9
galvanized nipple run:													
356-256	1/2"	1	1	1	1	1	1	1	1	1	1	1	11
356-257	3/4"	1	1	1	1	1	1	1	1	1	1	1	11
356-258	1"	1	0	1	1	1	1	1	1	1	1	1	10
356-259	1-1/4"	1	0	1	1	1	1	1	1	1	1	1	10
356-268	1-1/2"	1	0	1	1	1	1	1	1	1	1	1	10
356-269	2"	1	0	0	1	1	1	1	1	1	1	1	9
black 25-piece assortment:													
355-240	1/2"	4	3	3	3	2	2	2	1	2	1	2	25
355-241	3/4"	6	0	4	3	2	2	2	1	2	1	2	25
355-242	1"	5	0	5	3	2	2	2	1	2	1	2	25
galvanized 25-piece assortment:													
356-240	1/2"	4	3	3	3	2	2	2	1	2	1	2	25
356-241	3/4"	6	0	4	3	2	2	2	1	2	1	2	25
356-242	1"	5	0	5	3	2	2	2	1	2	1	2	25
black 66/60 pack assortment:													
355-246	1/2"	6	6	6	6	6	6	6	6	6	6	6	66
355-247	3/4"	6	6	6	6	6	6	6	6	6	6	6	66
355-248	1"	6	0	6	6	6	6	6	6	6	6	6	60
355-249	1-1/4"	6	0	6	6	6	6	6	6	6	6	6	60
galvanized 66/60 pack assortment:													
356-246	1/2"	6	6	6	6	6	6	6	6	6	6	6	66
356-247	3/4"	6	6	6	6	6	6	6	6	6	6	6	66
356-248	1"	6	0	6	6	6	6	6	6	6	6	6	60
356-249	1-1/4"	6	0	6	6	6	6	6	6	6	6	6	60