

SUBMITTAL SHEET

JOB NAME	ITEM TAG
JOB LOCATION	PART NUMBER
CONTRACTOR	DATE
ENGINEER APPROVAL	DATE

NO LEAD QUARTER-TURN BALL-TYPE CHROME SUPPLY STOP

T-596NL

Quarter-turn, self-cleaning ball valve design resists mineral and scale build-up, assuring positive shutoff and re-opening.

The ball-seat operation and dual O-ring stem seal outperform traditional multi-turn stop designs.

Compact, forged brass, chrome plated, or polished brass bodies are both durable and decorative.

An ideal upgrade replacement for worn, leaking stops that won't close completely.

Available in six straight-pattern configurations, including PEX, compression, and sweat inlet connections.



Pictured:
FNPT inlet connection

Working Pressure, Non Shock (PSI)

Cold working pressure (CWP): 125 CWP
Maximum service temperature: 180° F*

*Temperatures above 120°F increase the risk of scalding. Consult local code for temperature requirements.

MATERIAL SPECIFICATION	
PART	MATERIAL
1 Handle screw	Plated carbon steel
2 Handle	Chrome plated ABS
3 Stem	No lead brass
4 Stem O-ring (2)	NBR (Buna-N) rubber
5 Compression ferrule	Brass
6 Compression nut	Chrome plated brass
7 Body	No lead brass
8 Seat (2)	EPDM rubber
9 Ball	No lead brass
10 End adapter	No lead brass
11 Compression ferrule (compression inlet only)	Brass
12 Compression nut (compression inlet only)	Chrome plated brass
13 Compression nut (CPVC adapter inlet only)	Chrome plated brass
14 Adapter gasket (CPVC adapter inlet only)	NBR (Buna-N) rubber
15 Socket adapter (CPVC adapter inlet only)	Virgin CPVC resin
16 PEX barb adapter (PEX inlet only)	No lead brass

DIMENSIONS - Inch		
Size	A	B
3/8" FIP x 3/8" OD	1.10	2.01
1/2" FIP x 3/8" OD	1.10	2.17
5/8" OD x 3/8" OD*	1.10	2.44
1/2" CPVC x 3/8" OD	1.10	2.76
1/2" PEX x 3/8" OD	1.10	2.24
1/2" PEX x 1/2" PEX	1.10	2.24
1/2" SWT x 3/8" OD	1.10	2.40
Icemaker Options:		
5/8" OD x 1/4" OD	1.10	2.37
1/2" PEX x 1/4" OD	1.10	2.17


* Available in chrome plated or polished brass finishes

Certifications/Listings:


Third-party certified.
NSF/ANSI 61: Drinking water system components health effects.
NSF/ANSI 372: Drinking water system components lead content.

Standards:


ANSI/ASME B1.20.1: Pipe threads, general purpose (inch)
ANSI/ASME B16.18: Cast copper alloy solder joint pressure fitting.
ASTM F 1807: Metal insert fitting with crimp connection.




Pictured:
FNPT inlet connection




Pictured:
5/8" O.D. compression inlet




Pictured:
PEX barb inlet connection (crimp-ring, part number 460-903 sold separately)



Pictured:
PEX x PEX barb connections (crimp-ring, part number 460-903 sold separately)



Pictured:
CPVC solvent-weld inlet connection



Pictured:
Sweat tubing inlet connection