



**Certifications/Listings:**

Third-party certified

ANSI Z21.15 / CSA 9.1: Gas appliance connector valve for ½ lb. systems. (1/4" - 2" NPT)

ASME B16.44 / CGA CR91-002: For use in above ground gas piping systems up to 5 PSI. (1/4" - 4" NPT)

ASME B16.33 / B16.38: For use in gas piping systems up to 125 psi. (1/4" - 4" NPT)

CSA 3.16: For use in gas piping systems up to 125 psi. (1/4" - 4" NPT)

UL 3LZW: For use with LP, natural and manufactured gases; flammable liquids, #6 oil at 250° F (1/2" - 2" NPT)

UL MHKZ: Manual shutoff valve, 600 psi max. (1/2" - 2" NPT)

UL YQNZ: Compressed gas shutoff valve, 600 psi max. (1/2" - 2" NPT)

UL YRBX: Flammable liquid shutoff valve. 400 psi max. (1/2" - 2" NPT)

UL YRPV: Gas shutoff valve, 600 psi max. (1/2" - 2" NPT)

UL YSDT: LP gas shutoff valve, 600 psi max. (1/2" - 2" NPT)

Factory Mutual: Approved for fire protection service. (1/2" - 2" NPT)

**Standards:**

MSS SP-110: Ball Valves Threaded, Socket-Welding, Solder Joint, Grooved and Flared Ends.

ANSI/ASME B1.20.1: Pipe threads, general purpose, Inch.

ANSI/ASME B16.18: Cast Pressure alloy solder-joint pressure fittings.